

AquaNox 300/350/450 - Nox *Filter with 6-way valve*



Filter system

The Aquanox filter systems were especially designed for above-ground pools with hose connections. Nevertheless, they have all the features and comfort of larger filtration systems. The system stands securely on a stable base plate.

The system can be placed even on uneven grounds due to their compact design.

The Nox pump is self-priming and has a filter basket. By loosening the coupling ring on the suction nozzle (transparent cover), the filter basket can be easily removed for cleaning purposes. The system is delivered ready to plug in. Fully pre-assembled!



NEW from 2020:

All Filtersystems are mounted with rubberhose and filterstar.



connection 38 mm



connection 50 mm




technical data

technical data 230 V/ 50 Hz	A 1~ 230V	P1 [kW]	Connection // Pump suction	Flow rate in [m ³ /h] at 8 mWC	Connection Filter Tank Valve	Filtertank area in [m ²]	Weight without sand [kg]	Sand filling 0,4–0,8 mm [kg]
AquaNox 300 Nox 25-6 M	1,53	0,32	38mm*	4,5	1½" IG	0,09	14	25
AquaNox 350 Nox 25-6 M	1,53	0,32	38mm*	4,5	1½" IG	0,10	14	35
AquaNox 350 Nox 30-8 M	2,0	0,45	2¼" AG // 50/38 mm	5,4	1½" IG	0,10	14	35
AquaNox 450 Nox 50-12 M	2,8	0,65	2¼" AG // 50/38 mm	9,3	1½" IG	0,16	18	75

System	Dimension base	code
AquaNox 300 Nox 25-6 M	50 x 50 cm	772031801300
AquaNox 350 Nox 25-6 M	50 x 50 cm	772031801350
AquaNox 350 Nox 30-8 M	50 x 50 cm	772031811350
AquaNox 450 Nox 50-12 M	68 x 50 cm	772031821450

Dimensions

Model	A	B	C
Aquanox 300	800	230	500
Aquanox 350	800	215	500
Aquanox 450	900	215	680



* For Nox 25 6M another suction nozzle is available, **Fitting is not included**