

High flow rate filtration groups



Performance, reliability, design

PPF FILTRATION GROUPS

A comprehensive range of sand filters to meet all of your needs. Robust and reliable, combining excellent performance levels with low annual operating costs. Their clean, compact design makes them ideal for above-ground pools.

PPF85 – 200 – high flowrate filtration group

Technical data

- » Light grey, high density polyethylene sand filter;
- » Pump with prefilter;
- » Flexible pump/ filter connection kit, Ø 32–38 mm unions;
- » 6-way valve (PPF85 and 200) incorporated into the top section of the filter fitted with 3 solvent inlet/ outlet ports;
- » Bar laterals, 6-branch manifold with drain;
- » Black base delivered as standard.
- » The filters are delivered without the filter medium (use sand with a grain size of 0.4 to 0.8 mm).



	Description	Filtration capacity	Valves	Outer diameter	Pool volume	Quantity of sand	Pump	Power	Packaging dimensions	Gross weight
1	PPF85/19000WP	10 m ³ /h	6-way	476 mm	60/70 m ³	75/80 kg	WP19000	550 W	79 × 53 × 76 cm	24 kg
2	PPF200/21000WP	15 m ³ /h	6-way	646 mm	80/100 m ³	150/160 kg	WP21000	750 W	111 × 78 × 67 cm	31.6 kg

PPF15 – 65 filtration group

Technical data

- » Light grey, high density polyethylene sand filter;
- » Pump with prefilter;
- » Flexible pump/ filter connection kit, Ø 32–38 mm unions;
- » 4-way valve (PPF15, 25 and 45) or 6-way valve (PPF45 and 65) incorporated into the top section of the filter fitted with 3 solvent inlet/ outlet ports;
- » Bar laterals, 6-branch manifold with drain;
- » Black base delivered as standard (mini base for the PPF15 and PPF25 models).
- » The filters are delivered without the filter medium (use sand with a grain size of 0.4 to 0.8 mm).



	Description	Filtration capacity	Valves	Outer diameter	Pool volume	Quantity of sand	Pump	Power	Packaging dimensions	Gross weight
1	PPF15/3600SP	3,6 m ³ /h	4-way	252 mm	<20 m ³	13/15 kg	SP3600	140 W	45 × 26 × 41	8 kg
2	PPF25/4001SP	4 m ³ /h	4-way	334 mm	20/30 m ³	20 kg	SP4000	250 W	57 × 35 × 41	10.6 kg
3	PPF45/7000WP	6 m ³ /h	6-way	396 mm	35/45 m ³	25/30 kg	PP7000	400 W	71 × 42 × 51	14.7 kg
4	PPF65/8000WP	8 m ³ /h	6-way	476 mm	45/55 m ³	50/60 kg	SP8000	450 W	79,5 × 53,5 × 63	18 kg



BWT

**CHANGE
THE WORLD**

sip by sip



Dealer's stamp: