

TROPIC OCTO+ 450

ABOVE-GROUND ONLY

A pool is not a luxury anymore!

Solid, class IV treated pine structure, P-FI filtration group, easy to install, removable access ladder, class IV treated pine coping, **dark blue 0.50 mm** liner.

less than 10 m²

Height 120 cm



Ladder and pump



Filter



Liner



Wooden structure
Pool fittings

STANDARD COMPLIANT EQUIPMENT

All Proswell pools are compliant with the relevant French and European standards:

- **NF EN 16582-1** | Private family pools/ Part 1: general safety requirements and test methods.
- **NF EN 16582-2** | Private family pools/ Part 2: general safety requirements and test methods specific to in-ground pools.
- **NF EN 16582-3** | Private family pools/ Part 3: general safety requirements and test methods specific to above-ground pools.
- **NF EN 16713-1** | Private family pools/ Water distribution systems - Part 1: Filtration systems/ Requirements and test methods.
- **NF EN 16713-2** | Private family pools/ Water distribution systems - Part 2: Circulation systems/ Requirements and test methods.
- **NF EN P90-303** | Small pools - safety requirements and test methods.

Accreditation testing is carried out by an independent laboratory that may, if it is deemed necessary, require modification of the equipment or the installation instructions, and/or in our own laboratory.

Once all tests have been successfully passed, the laboratory issues a certificate of compliance for each pool model tested.

Procopi is PEFC certified (chain of custody: FCBA/12-01382) for procurement of wood from sustainably managed forests according to the regulations set out by the Programme for the endorsement of Forest Certification.

The PEFC label pertains to wood sourced from European forests.

CTB-B+ SP accredited (SP: this denomination was created for CTB-P+ and CTB-B+ certifications to denote enhanced retention of organic copper type products) by the CTBA.



27114205

Wooden pool Tropic Octo+ 450
Solid Northern Pine, Dark blue,
Height: 120 cm



ProSwell
by PROCOPI

Price
exVAT





TROPIC OCTO+ 450

ABOVE-GROUND ONLY

Less than 10 m²
Height 120 cm



ASSEMBLY



Model	Octo+ 450
Supplier reference	27114205
EAN13	3566837097288
Outer dimensions (cm)	452 x 313 cm
Inner dimensions (cm)	416 x 277 cm
Height, coping included (cm)	120 cm
Water volume (m ³)	10.66
Water surface area (m ²)	9.89
Packaging	2 pallets

STANDARD EQUIPMENT



ladder,
Liner
and Pump



Filter



Wooden
structure,
Pool fittings

Description	
Single width pine coping, thickness 28 mm, width 195 mm	included
Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1 mm	45
Liner thickness	0.50 mm
Liner colour	dark blue
Number of skimmers P-PM Body	1
Number of return fittings	1
Hydraulic fittings, 38 mm, not buriable	included
Sand filter	P-FI

Description	
Sand filter diameter (mm)	400
Flow rate at the return fitting (m ³ /h)	5.20
Quantity of sand provided (kg)	25
6-way valve (filtration/back-wash/rinse/circulation/drain/closed)	included
Stainless steel in-pool ladder	3 treads
Wooden, safety, access ladder	4 treads
Underlay	included
Installation instructions	included