



A hassle-free,  
practical range!  
The accessible  
dream!

ABOVE-GROUND | PARTIALLY IN-GROUND | IN-GROUND

# Pools for everyone!

ABOVE-GROUND | PARTIALLY IN-GROUND | IN-GROUND



## LADDERS

- » SS in-pool ladder, 3 treads,
- » Wooden access ladder, 4 to 5 treads.



## COPING

- » Made of class IV treated pine, thickness 28mm and width 290mm (2 × 145mm).

## LINER

- » 0.75mm liner, Dark blue



## RETURN FITTINGS AND SKIMMERS

- » 1 or 2 return fitting(s)
- » 1 or 2 skimmer(s)



## FILTRATION GROUP

- » Flow rate 7.90 to 9.70m<sup>3</sup>/h at the return fitting outlet(s) (depending on the model),
- » Sand filter, Ø 500 P-FI, anti-UV treated
- » 6-way valve (filtration/back wash/rinse/circulation/drain/closed)
- » Isolating valves on the return and suction lines,
- » Filtration pump fitted with a prefilter; power 0.46 to 0.60kW,
- » Semi-rigid, buriable hydraulic fittings, Ø 45mm.



## INTERLOCKING STRUCTURE

- » Class IV treated Northern pine, rounded finish
- » Thickness, 45mm,
- » Galvanised steel supporting brace for elongated octagonal, square and rectangular pool models.



## UNDERLAY

- » Underlay to be laid under the liner.



## STANDARD COMPLIANT EQUIPMENT

Every BWT myPOOL complies with the pool kit standards in effect, including the French standards that came into effect in February 2011:

- » NF P90-316 | Private family pools – pool kits – general safety requirements and test methods.
- » NF P90-317 | Private family pools – means of access – general safety requirements and test methods.
- » NF P90-318 | Private family pools – filtration groups and/or filtration systems – general safety requirements and test methods.

Accreditation tests are carried out by an independent laboratory that is entitled to demand modifications to the equipment or the installation instructions should it deem this to be necessary. Once all tests have been passed, the laboratory issues a certificate for each pool model tested.

BWT is PEFC certified (chain of custody: FCBA/12-01382) for procurement of wood from sustainably managed forests according to the regulations set out by the Programme for the Endorsement of Forest Certification.

THE PEFC label pertains to wood from European forests.

CTB-B+ SP labelled by CTBA (SP: this denomination was created for CTB-P+ and CTB-B+ certifications to designate enhanced retention of organic copper type products).



Structure  
Pool fittings



Filter



Ladder  
Pump  
Liner

# Pools for everyone!

ABOVE-GROUND | PARTIALLY IN-GROUND | IN-GROUND



Description	Details
Outer dimensions (cm)	843 × 489
Inner dimensions (cm)	789 × 435
Height coping included (cm)	133
Water volume (m <sup>3</sup> )	37.53
Water surface area (m <sup>2</sup> )	31.02
Packaging	2 pallets

## STANDARD EQUIPMENT

Description	
Metallic structural braces	6
Coping made of composite wood, thickness 35mm, width 285mm	included
Planks of solid, class IV treated Northern Pine, thickness in mm, tolerance + or - 1mm	45
Liner thickness	0.75mm
Liner colours	Dark blue
Number of skimmers P-PM body	1
Number of skimmers P-PM body	1
Buriable hydraulic fittings, Ø 45mm	included
Sand filter	P-FI

Description	
Sand filter diameter (mm)	500
Flow rate at the return fitting (m <sup>3</sup> /h)	8.30
Sand supplied (kg)	50
6-way valve (filtration/ backwash/ rinse/ circulation/ drain/ closed)	included
1/4 turn valve, return/ suction	included
In-pool SS ladder	3 treads
Wooden, safety, access ladder	4 treads
Underlay	included

27128210

Wooden pool Weva Octo +840  
Double pine, Dark blue liner, Height: 133 cm



Price  
inclVAT



bwt.com